

DRAKE TRAILERS PTY LTD

ENGINEERING BUILD SHEET

Customer:		Model: 4 x 8 LD S/WING ENCLOSED DECK CPA-11325	
Order No:	Serial No: 48157	Date Quoted: 03/03/2003	TARE:
Job No: 02-91	V.I.N. : 6T9T25ABJ30AKG037	CPA:	Variant:

<p>Deck Length: 12.625M MUST BE 25M @ 3.5 WIDE</p> <p>Widths: 2.7/3.0/3.45/3.7 /4.0/4.3/4.6M</p> <p>Deck Style:</p> <p>Goose Neck Type:</p> <p>Suspension: DRAKE HYD</p> <p>Axle Spacings: 1.2M - 2.4M - 1.2M</p> <p>Susp. Rams: DRAKE 4.5"</p> <p>Ram Seals: TEFLON</p> <p>Axles: YORK 15" 10 STUD 225PCD</p> <p>Slack Adj Lgth: 152mm CMA No: 9283 SS</p> <p>Brake Kit: PBR EBS: CMA No: 6900FB</p> <p>Chamber: 24/30 CMA No: 8991 CS</p> <p>King Pin Type: LIFT OUT 50MM & 90r Pin Size: 50 & 90mm</p> <p>Ball Race Block: NA</p> <p>Skid Plate Type: LEVEL OSCILLATING Blocked: No</p> <p>No of Pin Pos.: 3</p> <p>Couplings-Type: PBR</p> <p>Position: FRONT</p> <p>P/Mover Wheel:</p> <p>Tyre Carrier: 2 OFF DOUBLE VERTICAL SINGLE TRUCK FLAT BEHIND</p> <p>Widening Ram: P.T.E. BLC 4x18</p> <p>Push Point: No Pin Size:</p> <p>Greasing System: Full: No</p> <p>Hubo Fitted: No</p>	<p>No. Plate Pos: STD</p> <p>Mud Flaps: STD</p> <p>Mud Flap Colour:</p> <p>Ramps: 2.65M x .900M C/W HOLES</p> <p>Power Pack: 9HP HONDA DIESEL ELECTRIC/PULL START</p> <p>Pump Size: HAND PUMP BACKUP</p> <p>Tool Box: 2 LOCKABLE BUILT INTO FRAME</p> <p>Dunnage Trays:</p> <p>Water Tank: YES ON G/NECK</p> <p>Tyres: 215/75 x 17.5</p> <p>Tyre Brand: MICHELIN Steel/Alloy: Steel</p> <p>Rims: 6.0 x 17.5 10 Qty: 40 STUD 225 PCD</p> <p>Lights/Fittings: 12 VOLT HELLA</p> <p>Colour-Coamings: OLD CAT Goose: & COAMING YELLOW YELLOW C/W WHITE STRIPE</p> <p>Underside: SAME Hubs: SAME</p> <p>Wheels: SILVER Ramps:</p> <p>Deck:</p> <p>Sign Writing:</p> <p>P/Mover T/Table /Height: 1380M/T - Type:HOLLAND FW7C 1350 LOADED</p> <p>Dolly T/Table Height: Type:</p> <p>Swing Radius: 1900mm Height Radius: 840mm</p> <p>Distance (L): 6550mm Height of Guards:</p> <p>Hyds to Dolly: No Dolly Brand:</p> <p>Yard Release Kit: Dolly Type:</p>
--	--

Notes:

FULL REAR DECK, PLUMB HYDS TO DOLLY SO CAN BE OPERATED FROM TRAILER, TIE DOWN POINTS IN DECK, FIT HUBOMETER, TRUCK SPARE JUST LUG ON G/NECK BEHIND TRAILER SPARES, FIT BATTERY TO TRAILER FOR P/PACK, AXLE LIFT KITS ON ALL AXLES, HYD OPERATED RAISE & LOWER GOOSENECK, TWO OFF FLASHING LIGHTS ON RAMPS, 4 OFF DUNNAGE TRAYS IN CENTRE SECTION, EXTRA PROTECTION FOR TAILLIGHTS AND NUMBER PLATE LIGHTS, SIGN WRITING INCLUDED, TOW POINT ON BUMPER, PRESSURE GAUGE FITTED TO SUSP, SPECIAL TIEDOWN LUGS ON CENTRE SECTION, INNER & OUTER DECKS, FULLY ENCLOSED REAR DECK AND FRONT DECKS AS WIDE AS POSSIBLE, 50 & 90mm K/PINS PERMANANTLY CHAINED TO G/NECK, EXTRA SUPORT FOR LANDING LEGS, FITTING IN REAR AIR TANKS FOR RATTLE GUN, PLUG-IN ELECTRICS ON RAMPS

Entered By: _____	Date: _____
Reviewed by General Manager: _____	Date: _____
Approved by Engineering: _____	Date: _____