

Hazard Register



Type	VACUUM TRUCK	Location	
Make	-	Sale Number	8015000
Model	-	Lot Number	25
Serial Number			

ID	Hazard Type	Hazard Description
130984.1	Skills	Ensure only competent / skilled / trained personnel have access to and use of plant.
130984.2	Plant Maintenance	Not isolating, de-energising plant before commencing cleaning and/or maintenance activities.
130984.3	Emergency Stop	Failure of emergency stop switches (all emergency stop switches should be regularly tested in accordance with the original manufactures specifications).
130984.4	High Pressure Fluid	Person may come into contact with fluids under high pressure, due to plant failure or misuse of the plant.
130984.5	Crushing	Contact with moving parts of the plant during testing, inspection, operation, maintenance, cleaning or repair of the plant.
130984.7	Signage	Operator injury may result from illegible or missing warning labels/signage (noise, PPE, operating instructions, hot surfaces, exits, rotating fans, nip points etc). Regular inspection and replacement of warning labels (SAFETY DECALS) is required.
130984.8	Manual Handling	Operator strains and/or sprains as a result of repetitive body movements - handling of rear mounted suction hose
130984.9	Noise	SOUND PRESSURE LEVELS (SPL) NEEDS TESTING AT OPERATOR STATION. IF SPL GREATER THAN 85 dB(A), CLEAR & VISIBLE WARNINGS MUST BE ATTACHED RE: USE OF HEARING PROTECTION.
130984.10	Plant Controls	Operator injury can result from poorly labelled/ unlabelled or incorrectly labelled controls. Ensure all operational controls are clearly identified and labelled.
130984.11	Plant Operation	Ensure operator is provided with Standard Operating instructions - attach instruction in a clear and prominent position at operator's station.
130984.12	PPE	Operator injury resulting from not wearing provided PPE, wearing poorly maintained PPE, wearing insufficient or inappropriate PPE
130984.13	Guarding	Moving parts may entrap or cut body parts. All fixed and operable guards must be replaced after maintenance / cleaning activities. Guarding should be in accordance with Australian standard: safe guarding of machinery.
130984.14	M.S.D.S	OBTAIN MSDS FOR CHEMICALS USED AS WORK COOLANT AND LUBRICANT. CONDUCT RISK ASSESSMENTS IF CHEMICAL IS HAZARDOUS AS REQUIRED BY REGULATIONS
130984.15	Fire	FIRE EXTINGUISHER TO BE FITTED AND INSPECTED 6 MONTHLY.
130984.16	PLANT DAMAGE	ENSURE THAT A QUALIFIED PERSON INSPECTS THIS PLANT PRIOR TO USE IN THE WORKPLACE.
130984.17	Confined Space	IDENTIFY ALL OPERATIONAL HAZARDS ASSOCIATED WITH PLANT, RISK ASSESS IDENTIFIED HAZARDS AS PER AS4360:2004 RISK MANAGEMENT AND IMPLEMENT APPROPRIATE CONTROLS. DOCUMENT ALL RISK ASSESSMENTS.
130984.18	Safe Operating Procedures	AN EMPLOYER MUST PERFORM MAINTENANCE, INSPECTION AND CLEANING ON PLANT IN ACCORDANCE WITH THE MANUFACTURER'S AND DESIGNER'S REQUIREMENTS AND MUST PUT IN PLACE THE NECESSARY FACILITIES AND SYSTEMS OF WORK TO ENSURE THE SAFETY OF PERSONS WHO PERFORM THE MAINTENANCE, INSPECTION AND CLEANING . IF ACCESS TO THE PLANT IS REQUIRED TO PERFORM THESE TASKS, THE PLANT MUST BE STOPPED AND ONE OR MORE OF THE FOLLOWING MEASURES MUST BE USED TO CONTROL THE RISKS , LOCKOUT OR ISOLATION

Hazard Register



		DEVICES, DANGER TAGS , PERMIT TO WORK SYSTEMS OR OTHER CONTROL MEASURES.
130984.19	Plant Structure	Ensure Platforms, rails and ladders on this plant are compliant with Australian standard: Fixed Platforms, Walkways, Stairs, Ladders.
130984.20	Plant Operation	Ensure that one audilble and one visual warning device is present.

Health and Safety
Plant Safety
Purchaser Information

This plant health and safety information has been prepared by Grays for the purchaser of the plant item as required by National WHS Legislation. Whilst every effort has been made to identify all of the hazards, it should be recognised that all reasonably practicable hazards have been identified given due consideration to:

- state of knowledge about the plant item
- the availability and suitability of ways to eliminate or control the hazards
- the cost of evaluating, eliminating or controlling the hazard

Consequently, if this plant item is being purchased for use at a place of work, the purchaser is reminded of their obligations to involve and consult with employees in identifying foreseeable hazards, assess their risks and to take action to eliminate or control the risks.

In order to assess the risk, it is necessary to consider for all the identified hazards, the chance (likelihood) of something happening that would impact (consequence) on health and safety at the workplace. The following guidelines are provided to assist the purchaser in consistently carrying out an assessment of risk:

Likelihood	Consequences
• Frequency and duration of exposure • Probability of occurrence of hazard or event (including part history of incidents) • Possibility to avoid / minimize or limit the damage, impact or harm • Reliability and effectiveness of existing / established systems of control	• Assume “worst case” injury, but also competent follow-up medical and rehabilitation support • Consider forces or energy levels, highest belt tensions, size of gears, pulleys or other entrapment points and therefore body parts likely to be injured • Consider sharpness of entrapment points, surrounding parts likely to exacerbate injury, and any give in the entrapment point • Consider, will entrapment continue until plant is stopped, or can an injured part travel through the entrapment area • Are temperatures of plant, or chemicals, likely to further injure entrapped person

The outcome of the risk assessment will be a prioritised list of risk control strategies and actions consistent with the following ratings:

- Low risk- may be considered acceptable, where the existing controls in place are seen to be effective, requiring periodic monitoring for effectiveness.
Medium risk- considered to be unacceptable and requiring additional risk controls within medium to long term.
High risk – considered to be unacceptable and requiring action within the short to medium term.
Extreme risk – unacceptable, where immediate action required.

In all of these cases employees/operators must be made aware of the risk controls in place to protect them from the hazards.