

Hazard Register



Type	BULLDOZER	Location	
Make	-	Sale Number	1967
Model	-	Lot Number	
Serial Number			

This plant should be mechanically inspected by a competent person prior to being used and requires regular service and maintenance. All maintenance records should be kept as proof of regular service. Only experianced and competent operators should load, unload, maintain and operate this plant. Inexperianced operators should be under direct supervision at all times.

ID	Hazard Type	Hazard Description
142890.1	ENTANGLEMENT.	HAIR, CLOTHING, GLOVES, JEWELLERY, TOOLS, RAGS OR OTHER MATERIALS OR BODY PARTS MAY BECOME ENTANGLED WITH MOVING PARTS OF THE BULLDOZER SHOULD OPERATOR, MAINTENANCE PERSONNEL OR BYSTANDERS GET TO CLOSE TO THE MOVING PARTS OF THE BULLDOZER.
142890.2	CRUSHING.	OPERATORS, MAINTENANCE PERSONNEL AND BYSTANDERS OR THEIR BODY PARTS CAN BE CRUSHED DUE TO MATERIAL FALLING OFF THE BULLDOZER; UNCONTROLLED OR UNEXPECTED MOVEMENT OF THE BULLDOZER; LACK OF ABILITY FOR THE BULLDOZER TO BE SLOWED, SHOPPED OR IMMOBILISED; THE BULLDOZER TIPPING OR ROLLING OVER; PART OF THE BULLDOZER COLLAPSING; COMING IN CONTACT WITH MOVING PARTS OF THE BULLDOZER DURING SETUP, TESTING, INSPECTION, OPERATION, MAINTENANCE, CLEANING AND REPAIR; OPERATORS BEING THROWN OFF OR UNDER THE BULLDOZER; BEING TRAPPED BETWEEN PARTS OF THE BULLDOZER OR THE BULLDOZER AND MATERIALS OR FIXED STRUCTURES.
142890.3	CUTTING, STABBING OR PUNCHING	FINGERS, HANDS, ARMS AND OTHER BODY PARTS CAN BE CUT, STABBED OR PUNCHED DUE TO COMING IN CONTACT WITH SHARP OR FLYING OBJECTS; COMING IN CONTACT WITH MOVING PARTS OF THE BULLDOZER DURING OPERATION, MAINTENANCE, CLEANING AND REPAIR OF THE BULLDOZER; THE MOBILITY OF THE BULLDOZER AND THE UNCONTROLLED OR UNEXPECTED MOVEMENT OF THE BULLDOZER.
142890.4	SHEARING.	PEOPLE WORKING AROUND THE BULLDOZER CAN HAVE FINGERS, HANDS AND OTHER BODY PARTS SHEARED BETWEEN TWO PARTS OF THE BULLDOZER, OR BETWEEN A PART OF THE BULLDOZER AND THE LOAD OR ANOTHER STRUCTURE.
142890.5	STRIKING.	OPERATORS OR BYSTANDERS CAN BE STRUCK BY MOVING OBJECTS DUE TO THE UNCONTROLLED OR UNEXPECTED MOVEMENT OF THE BULLDOZER; LACK OF ABILITY FOR THE BULLDOZER TO BE SLOWED, SHOPPED OR IMMOBILISED; OR MATERIAL HANDLED BY THE BULLDOZER BEING EJECTED OR FLYING OR FALLING OFF THE BULLDOZER.
142890.6	HIGH PRESSURE FLUIDS	OPERATORS, BYSTANDERS AND MAINTENANCE PERSONNEL CAN COME IN CONTACT WITH FLUIDS UNDER PRESSURE, DUE TO FAILURE OR MISUSE OF THE BULLDOZER OR LACK OF ISOLATION OR SAFE OPERATION PROCEDURES.
142890.8	ELECTROCUTION.	OPERATORS AND BYSTANDERS MAY BE BURNED OR ELECTROCUTED BY THE BULLDOZER CONTACTING OR BEING OPERATED IN CLOSE PROXIMITY TO OVERHEAD OR UNDERGROUND ELECTRICAL CONDUCTORS.

Hazard Register



142890.10	SLIP TRIP FALL	OPERATORS, BYSTANDERS AND PASSENGERS USING AND WORKING AROUND BULLDOZER CAN SLIP, TRIP AND FALL DUE TO UNEVEN OR SLIPPERY SURFACES ON AND IN THE VICINITY OF THE BULLDOZER.
142890.11	FALL FROM HEIGHTS	OPERATORS, BYSTANDERS, MAINTENANCE PERSONNEL AND PASSENGERS REQUIRED TO WORK ON THE TOP OF OR OUTSIDE OF THE BULLDOZER CAN FALL FROM HEIGHTS DUE TO LACK OF PROPER WORK PLATFORM; LACK OF PROPER STAIRS OR LADDERS; LACK OF GUARD RAILS OR OTHER EDGE PROTECTION; AND POOR WALKING OR WORK SURFACES, SUCH AS UNEVEN, STEEP OR SLIPPERY WORK SURFACES.
142890.12	ERGONOMICS.	OPERATORS AND PASSENGERS CAN BE INJURED DUE TO POORLY DESIGNED AND MAINTAINED SEATING AND OPERATOR CONTROLS THAT REQUIRE REPETITIVE BODY MOVEMENT; CONSTRAINED BODY POSTURE OR THE NEED FOR EXCESSIVE EFFORT; AND MISMATCH OF BULLDOZER WITH HUMAN TRAITS AND NATURAL LIMITATIONS.
142890.14	HIGH TEMPERATURE	OPERATORS, PASSENGERS AND MAINTENANCE PERSONNEL MAY BE BURNT BY COMING INTO CONTACT WITH PARTS OF THE BULLDOZER AT HIGH TEMPERATURES.
142890.15	FIRE.	OPERATORS, MAINTENANCE PERSONNEL AND PEOPLE REQUIRED TO REFUEL THE BULLDOZER CAN BE INJURED BY FIRE DUE TO FAILURE OR MISUSE OF THE BULLDOZER OR THE LACK OF SAFE OPERATION PROCEDURES.
142890.16	ENVIRONMENTAL TEMPERATURE	OPERATORS CAN SUFFER HEAT STRESS OR HEAT STROKE DUE TO PROLONGED EXPOSURE TO THE SUN OR HIGH TEMPERATURES.
142890.17	CHEMICALS, FUELS	EXPOSURE TO CHEMICALS (LPG, PETROL, DIESEL) THROUGH THE REFUELLING OF THE BULLDOZER CAN CAUSE IRRITATION TO THE EYES, NOSE, THROAT AND SKIN. WHILE PROLONGED EXPOSURE CAN CAUSE IRREVERSIBLE HEALTH ISSUES.
142890.18	FUMES.	OPERATORS CAN BE INJURED OR SUFFER ILL-HEALTH FROM PROLONGED EXPOSURE TO FUMES GIVEN OFF BY THE OPERATION OF THIS BULLDOZER.
142890.19	NOISE.	OPERATORS AND BYSTANDERS CAN BE INJURED OR SUFFER ILL-HEALTH FROM EXPOSURE TO NOISE LEVELS GREATER THAN 85db(A) CONTINUES OVER 8 HOURS OR 140db(C) PEAK, THROUGH THE OPERATION OF THIS BULLDOZER.
142890.20	VIBRATION.	OPERATORS AND BYSTANDERS CAN BE INJURED OR SUFFER ILL-HEALTH FROM EXPOSURE TO VIBRATION GIVEN OFF THROUGH THE OPERATION OF THIS BULLDOZER.
142890.23	EXCAVATION.	OPERATORS AND BYSTANDERS CAN BE INJURED DUE TO THE BULLDOZER COMING IN CONTACT WITH OR WORKING TO CLOSE TO UNDER GROUND CABLES AND PIPES.
142890.24	TRAFFIC MANAGEMENT.	BYSTANDERS AND PEOPLE REQUIRED TO WORK AROUND BULLDOZER CAN BE INJURED DUE TO THE LACK OF TRAFFIC MANAGEMENT PROCEDURES, BARRIERS, GUARDING AND SEPARATION OF PEDESTRIANS AND PLANT.
142890.25	PASSENGERS	PASSENGERS CAN BE SEVERELY INJURED OR KILLED AS A RESULT OF RIDING ON THE BULLDOZER WHERE A PASSENGER SEATS AND SEAT BELT IS NOT PROVIDED. PASSENGERS SHOULD NOT RIDE ON OR IN BULLDOZER WHERE A PASSENGERS SEAT AND SEAT BELT IS NOT PROVIDED. NEVER CARRY PASSENGERS ON THE LOAD HANDLING AREAS.
142890.26	PLANT OPERATION.	THE BULLDOZER SHOULD ONLY BE OPERATED BY COMPETENT, SKILLED AND TRAINED PERSONAL. ALL OPERATOR CONTROLS AND SAFETY SYSTEMS SHOULD BE TESTED PRIOR

Hazard Register



TO OPERATION AND ALL FAULTS REPORTED IMMEDIATELY. THIS BULLDOZER SHOULD NEVER NOT BE OPERATED WITHOUT ALL GUARDING IN PLACE AND ALL SAFETY SYSTEMS FUNCTIONING CORRECTLY.

142890.27 MAINTENANCE.

THE BULLDOZER SHOULD ONLY BE MAINTAINED BY COMPETENT, SKILLED AND TRAINED PERSONNEL AND ALL ENERGY SOURCES ASSOCIATED WITH THE BULLDOZER TO BE ISOLATED AND DE ENERGISED WHILE BULLDOZER IS BEING MAINTAINED. THE BULLDOZER SHOULD NOT BE PUT BACK IN SERVICE WITHOUT ALL GUARDS IN PLACE AND ALL SAFETY SYSTEMS TESTED AND OPERATIONAL.

142890.28 INFORMATION, INSTRUCTION, TRAINING & SUPERVISIONALL OPERATORS, MAINTENANCE PERSONNEL AND PEOPLE REQUIRED TO WORK ON THE BULLDOZER REQUIRE INFORMATION ON THE OPERATION AND HAZARDS OF THE BULLDOZER, INSTRUCTION AND TRAINING ON HOW TO OPERATE, CLEAN AND MAINTAIN THE BULLDOZER AND PERSONAL SHOULD ALWAYS BE SUPERVISED WHEN OPERATING, MAINTAINING OR REQUIRED TO WORK AROUND THE BULLDOZER.

Health and Safety
Plant Safety
Purchaser Information

This plant health and safety information has been prepared by Grays for the purchaser of the plant item as required by National WHS Legislation. Whilst every effort has been made to identify all of the hazards, it should be recognised that all reasonably practicable hazards have been identified given due consideration to:

- state of knowledge about the plant item
- the availability and suitability of ways to eliminate or control the hazards
- the cost of evaluating, eliminating or controlling the hazard

Consequently, if this plant item is being purchased for use at a place of work, the purchaser is reminded of their obligations to involve and consult with employees in identifying foreseeable hazards, assess their risks and to take action to eliminate or control the risks.

In order to assess the risk, it is necessary to consider for all the identified hazards, the chance (likelihood) of something happening that would impact (consequence) on health and safety at the workplace. The following guidelines are provided to assist the purchaser in consistently carrying out an assessment of risk:

Likelihood	Consequences
• Frequency and duration of exposure • Probability of occurrence of hazard or event (including part history of incidents) • Possibility to avoid / minimize or limit the damage, impact or harm • Reliability and effectiveness of existing / established systems of control	• Assume “worst case” injury, but also competent follow-up medical and rehabilitation support • Consider forces or energy levels, highest belt tensions, size of gears, pulleys or other entrapment points and therefore body parts likely to be injured • Consider sharpness of entrapment points, surrounding parts likely to exacerbate injury, and any give in the entrapment point • Consider, will entrapment continue until plant is stopped, or can an injured part travel through the entrapment area • Are temperatures of plant, or chemicals, likely to further injure entrapped person

The outcome of the risk assessment will be a prioritised list of risk control strategies and actions consistent with the following ratings:

- Low risk- may be considered acceptable, where the existing controls in place are seen to be effective, requiring periodic monitoring for effectiveness.
Medium risk- considered to be unacceptable and requiring additional risk controls within medium to long term.
High risk – considered to be unacceptable and requiring action within the short to medium term.
Extreme risk – unacceptable, where immediate action required.

In all of these cases employees/operators must be made aware of the risk controls in place to protect them from the hazards.