



Asset Hazard Register

GRAYSONLINE

As at March 19, 2013

Type: RIDE ON MOWER
Make: COX
Model: 09M7

Auction Venue: SALE NO 3002811
Lot number: LOT 26
Sale Date:

ID	Hazard Type	Hazard Description
1	Thermal Conditions	EXPLOSION/FIRE FROM ENGINE, SHUT OFF ENGINE AND LEAVE TO COOL BEFORE REFUELLING, PROVIDE FIRST AID KIT AND FIRE EXTINGUISHER FOR THE PLANT
2	Noise	SOUND PRESSURE LEVELS (SPL) NEEDS TESTING AT OPERATOR STATION, IF SPL GREATER THAN 85 dB(A 8hr) OR 140 dB(C PEAK), CLEAR AND VISIBLE WARNINGS MUST BE ATTACHED RE: USE OF HEARING PROTECTION, EXAMINE WAYS TO REDUCE EMISSIONS FROM THE PLANT AND ATTACH CLEAR AND VISIBLE WARNING SIGN RE: HEARING PROTECTION.
3	Process Manual	SUPPLY (IF AVAILABLE) MANUFACTURER'S OPERATING (INCLUDING PRE-OPERATIONAL CHECKS AND PERSONAL PROTECTIVE EQUIPMENT REQUIREMENTS) FOR THE OPERATOR.
4	Plant Operation	MOWER TO BE OPERATED BY COMPETENT OPERATORS ONLY
5	Plant Structure	SEEK TECHNICAL ADVICE FROM THE MANUFACTURER BEFORE CARRYING OUT ANY MODIFICATION TO THE MOWER (E.G. ADJUSTMENT TO WHEEL/RIDE HEIGHT, ETC)
6	Plant Operation	COLLISIONS WITH OTHER FIXED/MOBILE OBJECTS. PREPARE SAFE WORK PROCEDURES FOR USE IN AN ENVIRONMENT THAT MAY POSE A RISK OF COLLISION. USE ALL WARNING SYSTEMS FITTED TO THE PLANT (IE HORN).
7	Plant Operation	TO PREVENT COLLISION WITH PEDESTRIANS/BY STANDERS AND WHEN WORKING NEAR PUBLIC ROADS AND ACCESS WAYS, POST WARNING SIGNS AND PLACE BARRIERS ETC AROUND WORKING AREA

Asset Hazard Register

GRAYSONLINE

As at March 19, 2013

8	Mechanical	DO NOT STEP ON OR OFF MOVING PLANT, ONLY OPERATE FROM DRIVING POSITION.
9	Plant Operation	DEVELOP AND CONDUCT DOCUMENTED PRE-OPERATIONAL CHECKS PRIOR TO EACH USE.
10	Mechanical	ENTANGLEMENT/STRIKING BY WORKPIECES EJECTING FROM MOVING PARTS OF THE PLANT. THE DRIVE TO THE PLANT MUST BE STOPPED/DISCONNECTED AND MOVING PARTS OF THE PLANT STOPPED BEFORE MAINTENANCE AND REMOVING ANY OBSTRUCTIONS NEAR THE PLANT. DO NOT OPERATE IN THE VICINITY OF OTHER PEOPLE. IF THIS IS NOT POSSIBLE SUPPLY PPE TO THOSE PEOPLE TO PREVENT INJURY FROM STRIKING OBJECTS.
11	Work Space	SLIP/TRIP/FALL DUE TO CLIMATE CONDITIONS. WIPE CLEAR (BEFORE USING THE PLANT) IF THERE IS ANY MUD, OIL OR OTHER OBSTRUCTIONS ON THE PLANT.
12	Thermal Conditions	EXPOSURE TO OUTDOOR CLIMATE/WEATHER CONDITIONS. PROVIDE PERSONAL PROTECTIVE EQUIPMENT FOR WET, UV EXPOSURE, HOT OR COLD CONDITIONS.
13	PPE	PROVIDE INFORMATION/INSTRUCTION ON STORAGE, USE CARE AND MAINTENANCE OF PERSONAL PROTECTIVE EQUIPMENT.
14	Air Quality	EXHAUST EMISSION (CARBON MONOXIDE) MAY BE HARMFUL. ENSURE THE PLANT IS OPERATED IN A WELL VENTILATED AREA
15	Chemicals	OBTAIN MSDS AND CONDUCT AND DOCUMENT HAZARDOUS SUBSTANCE RISK ASSESSMENT FOR ALL CHEMICALS USED WITH THE PLANT (E.G. DIESEL, OILS ETC)
16	Rollover	DO NOT OPERATE PLANT ON UNEVEN OR SLOPED GROUND WHICH MAY POSE A RISK OF MOWER ROLLOVER.



Hazard Register

Occupational Health and Safety Plant Safety Purchaser Information

This plant health and safety information has been prepared by Graysonline for the purchaser of the plant item as required by National and State OHS Legislation. Whilst every effort has been made to identify all of the hazards, it should be recognised that such hazards have been identified given due consideration to the state of knowledge of the plant item.

If this plant item is being purchased for use at a place of work, the purchaser is reminded of their obligations to review the hazard register and in consultation with employees, prepare a formal risk assessment for the operation of the plant item in the new environment. In order to assess the risk, it is necessary to consider the likelihood of an incident that would impact (consequence) on health and safety at the workplace. The following guidelines are provided to assist the purchaser to complete the plant assessment.

Likelihood	Consequence
<ul style="list-style-type: none"> • Frequency and duration of exposure • Probability of occurrence of hazard or event (including part history of incidents) • Possibility to avoid / minimize or limit the damage, impact or harm • Reliability and effectiveness of existing / established systems of control 	<ul style="list-style-type: none"> • Assume “worst case” injury, but also competent follow-up medical and rehabilitation support • Consider forces or energy levels, highest belt tensions, size of gears, pulleys or other entrapment points and therefore body parts likely to be injured • Consider sharpness of entrapment points, surrounding parts likely to exacerbate injury, and any give in the entrapment point • Consider, will entrapment continue until plant is stopped, or can an injured part travel through the entrapment area • Are temperatures of plant, or chemicals, likely to further injure entrapped person

The outcome of the risk assessment is a prioritised list of risks and risk controls (existing and proposed) for further action based on the following risk ratings:

Low risk- may be considered acceptable, where the existing controls in place are seen to be effective, requiring periodic monitoring for effectiveness.

Medium risk- considered to be unacceptable and requiring additional risk controls within medium to long term.

High risk – considered to be unacceptable and requiring action within the short to medium term.

Extreme risk – unacceptable, where immediate action required.

In all of these cases employees/operators must be made aware of the risk controls in place to protect them from the hazards.