

Hazard Register



Type	TRENCH ROLLER	Location	Select
Make	GENERIC	Sale Number	0
Model	Generic	Lot Number	
Serial Number			

ID	Hazard Type	Hazard Description
143060.1	Skills	CRUSH INJURIES. ENSURE OPERATORS ARE TRAINED TO OPERATE ROLLER IN FORWARD DIRECTION. OPERATORS TO BE AWARE OF RISK OF REVERSING PLANT.
143060.2	Plant Operation	ATTACH CLEAR & VISIBLE OPERATING INSTRUCTIONS IN OPERATOR WORK AREA.
143060.3	Plant Operation	CONDUCT AND DOCUMENT REGULAR PLANT CONDITION INSPECTIONS
143060.4	Plant Operation	NO SERVICE OR MAINTENANCE RECORDS AVAILABLE
143060.5	Controls	OPERATOR CONTROLS TO BE CLEARLY LABELLED & IDENTIFIED
143060.6	Signage	ATTACH CLEAR & VISIBLE HAZARD WARNINGS REGARDING EXPOSED MOVING ROLLER ABLE TO CAUSE CRUSHING INJURIES TO FEET
143060.7	Noise	SOUND PRESSURE LEVELS NEED TESTING AT OPERATOR STATION. IF SPL GREATER THAN 85 dB(A), CLEAR & VISIBLE WARNINGS MUST BE ATTACHED re USE OF HEARING PROTECTION.
143060.8	PPE	ROLLER ABLE TO CAUSE CRUSHING INJURIES TO FEET. ENSURE CLOSED IN FOOT PROTECTION/SAFETY BOOTS ARE PROVIDED TO OPERATORS
143060.9	Skills	PLANT TO BE USED AND ACCESSED BY COMPETENT/SKILLED PERSONEEL ONLY.

Health and Safety Plant Safety Purchaser Information

This plant health and safety information has been prepared by Grays for the purchaser of the plant item as required by National WHS Legislation. Whilst every effort has been made to identify all of the hazards, it should be recognised that all reasonably practicable hazards have been identified given due consideration to:

- state of knowledge about the plant item
- the availability and suitability of ways to eliminate or control the hazards
- the cost of evaluating, eliminating or controlling the hazard

Consequently, if this plant item is being purchased for use at a place of work, the purchaser is reminded of their obligations to involve and consult with employees in identifying foreseeable hazards, assess their risks and to take action to eliminate or control the risks.

In order to assess the risk, it is necessary to consider for all the identified hazards, the chance (likelihood) of something happening that would impact (consequence) on health and safety at the workplace. The following guidelines are provided to assist the purchaser in consistently carrying out an assessment of risk:

Likelihood	Consequences
<ul style="list-style-type: none">• Frequency and duration of exposure• Probability of occurrence of hazard or event (including part history of incidents)• Possibility to avoid / minimize or limit the damage, impact or harm• Reliability and effectiveness of existing / established systems of control	<ul style="list-style-type: none">• Assume “worst case” injury, but also competent follow-up medical and rehabilitation support• Consider forces or energy levels, highest belt tensions, size of gears, pulleys or other entrapment points and therefore body parts likely to be injured• Consider sharpness of entrapment points, surrounding parts likely to exacerbate injury, and any give in the entrapment point• Consider, will entrapment continue until plant is stopped, or can an injured part travel through the entrapment area• Are temperatures of plant, or chemicals, likely to further injure entrapped person

The outcome of the risk assessment will be a prioritised list of risk control strategies and actions consistent with the following ratings:

Low risk- may be considered acceptable, where the existing controls in place are seen to be effective, requiring periodic monitoring for effectiveness.

Medium risk- considered to be unacceptable and requiring additional risk controls within medium to long term.

High risk – considered to be unacceptable and requiring action within the short to medium term.

Extreme risk – unacceptable, where immediate action required.

In all of these cases employees/operators must be made aware of the risk controls in place to protect them from the hazards.