

Textile Composite Flooring

FLASH - POP







VISIONARY LIVING COMMERCIAL FLOORS & WALLS

From our establishment in 1957, we have become one of the oldest exclusive manufacturers of *commercial flooring* in the United States. As one of the largest privately held mills, our FAMILY-OWNERSHIP provides a *heritage* of proven performance and expansive industry knowledge. Most importantly, our focus has always been on *people…* ensuring them that our products deliver the highest levels of BEAUTY, PERFORMANCE and DEPENDABILITY.

(cover) Flash Rojo, Pop Cielo and Propel II Outpace, quarter turn.
(right) Flash Verde and Pop Verde, quarter turn.





flash 1818



style 1818 **color 1720** mostaza



style 1818 **color 1721** verde



style 1818 **color 1722** esmeralda



style 1818 **color 1723** rojo



style 1818 **color 1724** violeta



style 1818 **color 1725** morado




style 1818 **color 1726** cielo




style 1818 **color 1727** turquesa



style 1818 **color 1728** azul



style 1818 **color 1729** anaranjado



pop 1816




style 1816 **color 1710** mostaza



style 1816 **color 1711** anaranjado



color 1712 rojo



style 1816 **color 1713** violeta



style 1816 **color 1714** morado



style 1816 **color 1715** verde



style 1816 **color 1716** esmeralda



style 1816 **color 1717** cielo



style 1816 **color 1718** turquesa



style 1816 **color 1719** azul

*Pop is to be used for borders, accents and insets only

Flash Cielo, Mostaza and Verde and Pop Cielo, Mostaza and Verde, quarter turn.

77

1


HIIII

Ш



colour line overview

flash 1818



1720 mostaza



1726 cielo

1710

1716

esmeralda

mostaza









1727

turquesa

1718 turquesa



1722 esmeralda



1728

azul



1723 rojo



1729 anaranjado



1724 violeta

1714

morado



1725 morado



1715 verde

1713 violeta



1719 azul



cielo

where to use kinetex

Healthcare

Acute care hospitals, medical office buildings, urgent care clinics, outpatient surgery centers, outpatient physical therapy/rehab centers, outpatient imaging centers, etc.

- Cafeteria, dining areas
- Chapel
- Computer room
- Corridors
- Diagnostic imaging suites
- Dry physical therapy
- Elevators
- Exam/procedure rooms
- · Gift shops
- Hyperbaric treatment rooms
- Lobbies
- Nursing stations
- Offices/administration / conference rooms
- Patient rooms (family areas)
- Pharmacy
- Ramps/ramped corridors
- Staff lounge
- · Waiting rooms

Education

Early childhood development centers, preschool, k-12, higher education

- Auditoriums
- Classrooms/lecture halls
- Computer classrooms
- Student Accommodation
- Food service areas
- Multipurpose rooms/cafetorium
- Ramps/ramped corridors
- Faculty/administrative offices
- Faculty lounge
- Libraries
- Innovation Hubs

Commercial Offices

Offices, call centers

- Offices
- Waiting areas
- Corridors
- Conference rooms
- Copy/mail rooms
- Break rooms · Computer rooms

Fitness Centers

Health Clubs/Gyms

- Cardio Centers
- Dry Locker Room Areas
- Snack Bars
- Offices

Retail / Mercantile

Wholesale/Retail merchants

- Checkout/cash wrap
- Dressing rooms
- Sales floor
- Offices
- Employee break areas

Hospitality

- Hotels
- Corridors
- Conference rooms
- Guest rooms
- Dining rooms
- Business centers
- · Activity rooms
- Common areas
- · Computer rooms

Transportation/

Public Venues

Airports, bus/train stations, performing arts centers, athletic arenas

- Ticketing/baggage claim
- Concourses
- Jetways
- Conference rooms
- Waiting areas
- Administrative offices
- Airport lounges
- Chapel
- Large public spaces
- Theaters

a unique floor covering alternative to hard-surface products, J+J Flooring Group's Kinetex encompasses an unprecedented range of performance attributes for retail, healthcare, education and institutional environments. In addition to its

human-centered gualities and highly functional design, Kinetex offers a reduced

environmental footprint compared to traditional hard-surface options.

The key to the high-performance attributes of Kinetex lies within its construction. Each layer, when used together, creates a versatile, lightweight, soft-surface flooring designed with qualities parallel to that of hard-surface.

Kinetex Construction

Wear Layer/Face Fiber Abrasion and Ravel Resistant Knitted Fabric

> Cushioned Backing Polyester Felt

Thermally Fused



kinetex overview


1. DURABILITY

Kinetex delivers enduring performance, year after year. One of the most thoroughly tested flooring products on the market, it has outstanding dimensional stability and unparalleled crush resistance.



3. MOISTURE TOLERANCE

The most common subfloor, concrete, can release excessive moisture and destroy floor covering systems—unless costly precautions are taken before installation. But moisture mitigation isn't necessary with Kinetex; its breathable nature allows moisture to pass through its backing, instead of trapping it underneath. Kinetex textile composite flooring will perform in elevated RH slabs up to 100%.



Coefficient of Friction

NESL


wet soapy surfaces


2. MAINTENANCE

Tough to wear out, easy to maintain. With vacuuming and encapsulation cleaning, Kinetex looks like new, year after year. Thanks to a lightweight face construction, Kinetex retains less water than carpet and dries faster. It is easily sanitized and resists the most challenging staining agents.

Life Cycle Costs:

INSTALLATION AND MAINTENANCE






Foot Traffic Dust Emissions Test (ESO Fine Test Dust 12103-142)

6. ACOUSTICS


Kinetex delivers unparalleled acoustic performance, with one of the highest Noise Reduction Coefficients (NRC) and Impact Insulation Classifications (IIC) ratings of any commercial flooring product.

Keeping Quiet



7. COMFORT

Kinetex, a soft textile surface with a high-density backing, has exceptional anti-fatigue properties and minimal rolling resistance. Because it can absorb energy, Kinetex has the potential to reduce repetitive foot stress injuries and other injuries related to standing and frequent movement from place to place.




8. SUSTAINABILITY

Made with 45% post-consumer recycled content, each Kinetex tile contains the equivalent of 27 used water bottles. This dematerialized flooring product and its longer life mean that Kinetex has a much smaller environmental footprint than other commercial flooring options. Furthermore, Kinetex is NSF/ANSI-140 Platinum certified (the industry-leading standard for sustainability) and has a Red List Free DECLARE label.

Second Chances





Each Kinetex tile contains the equivalent of 27 plastic water bottles.

KINETEX INSTALLATION

Installing Kinetex is as easy as traditional modular carpet, however special attention should be applied until installers gain experience with module placement. Installers should perform site and material conditioning, surface preparation, and concrete pH and moisture testing as if they were installing carpet modules. Because it is such a lightweight material the modules cut very easily, reducing installation time. Kinetex uses proven adhesive systems with lifetime performance warranties.

Kinetex Adhesive

Kinetex Adhesive is formulated for Kinetex textile composite flooring products and is built to bond the textile composite to the properly prepared substrates for the life of the installation. Products with Kinetex Adhesive will perform in elevated RH slabs up to 100%.

PreFix®

PreFix includes a release liner that easily peels away to reveal pre-applied adhesive that securely anchors the Kinetex module in place. Products with PreFix will perform in elevated RH slabs up to 100%, allowing the flooring to be installed without costly moisture mitigation. PreFix offers a quick installation system and it can be added to all Kinetex products as an optional adhesive.

Please see the Kinetex installation instructions for full installation details.

product details

product flexibilities

WARRANTIES

We stand behind every aspect of Kinetex and extend certain lifetime warranties. Each warranty is covered for the useful life of the product, provided that installation and maintenance is in accordance with J+J Flooring Group's Kinetex Installation Instructions.

Wear Layer Warranties

- Lifetime Product Performance
- Lifetime Colorfastness to Light & Crocking
- Lifetime Stain Removal
- Lifetime Static Protection

Backing Warranties

- Lifetime Protection from Edge Ravel
- Lifetime Protection from Delamination Failure
- Lifetime Dimensional Stability

ACCOLADES

Kinetex is one of the most extensively tested flooring products to ever be introduced. In addition to its unprecedented range of performance attributes, the human-centered qualities and highly functional design have quickly garnered attention. Below is a list of current awards and recognitions that Kinetex has received.


- 2015 Nightingale Award
- Gold, Hard Surface (Umbra / Umbra Stripe)
- 2015 Best of NeoCon, Hard Surface Silver Award (Umbra / Umbra Stripe) (Contract Magazine)
- 2014 Top Ten Green Building Product (BuildingGreen, Inc.)
- 2014 Greenstep Award (Floorcovering Weekly)
- 2014 Grand Prize Winner for Product Innovations (Buildings Magazine)
- 2014 Excellence in Product Development (British Institute of Facilities Management)

ADHESIVES

Kinetex® Adhesive

By design, Kinetex uses J+J Flooring Group's proven releasable Kinetex Adhesive with lifetime performance warranties. Because it is such a lightweight material, the modules cut very easily, reducing installation time. Kinetex also offers the flexibility to simply remove and replace individual modules if conditions warrant a quick fix.





PreFix is a quick installation solution for all Kinetex textile composite flooring products. The release liner easily peels away to reveal a series of pre-applied adhesive strips that securely anchor the Kinetex module in place.

Created specifically for Kinetex, PreFix preapplied releasable adhesive backing offers the following:

- Highest breathability (250 gms/sm/day) allows up to 99% RH and pH from 7 to 11
- No glue dry time from pre-cured no odor, VOCfree, 100% polymer adhesive
- Controlled USA manufacturing environment assures consistent aggressive tack quality
- Avoids glue inventory, glue transportation charges and disposal of empty buckets
- Recyclable release liner extended edge for easy removal
- Lifetime Warranty -Requires PreFix Primer

PreFix backing requires PreFix Primer during subfloor preparation

style

pop **1816** / flash **1818**

Phyical Characteristics	
wear layer	solution dyed polyester
backing	polyester felt cushion
total weight (nominal average)	1373 g – 1587 g sq/m
total thickness (nominal average)	5.2 mm
dimensions	610 mm x 610 mm tiles
packaging	eighteen modules per box, 6.69 sq/m
Environmental Attributes	
recyclability	100% closed-loop recyclable
recycled content	>55% (post consumer/industrial)
LEED scorecard	IEQ 4.1 and IEQ 4.3

platinum

NSF/ANSI 140 certification

Testing

fire test report	AS
critical radiant flux (CRF)	6.6
electrostatic propensity	les
colorfastness to light	rati
colorfastness to crocking	rati
water repellency	rati
appearance retention	4.0
slip resistance	A54
thermal insulation	0.73
noise reduction coefficient	NR
impact insulation classification	IIC
stain resistance	res

AS ISO 9239.1-2003 6.6kw/m2 less than 3.0 kv rating of 4.0 or greater rating of 4.0 or greater 4.0 or greater AS4586-2013 Class P5 0.73 NRC Rating: 0.30* IIC Rating: 64** resists most challenging stains

adhesives

indoor air quality certification

Installation Methods

CRI Green Label Plus™



©2016 J&J Flooring Group, LLC - This unique design is protected under the U.S. Copyright Act of 1976. Any unauthorized copying or duplication of this design constitutes copyright infringement in violation of federal law.

Due to the unique visual characteristics of modular carpets, pattern repeats and pattern run-off seams may appear more noticeable than in broadloom carpets. Such visual characteristics do not constitute a manufacturing defect, and as such, should be considered when selecting modular carpet and its installation.

These photographs are representations of the installation for this modular product. Your modular installation may look different than these photos depending upon individual tile placement, lighting, and overall space layout, including furnishings. Final tile placement and the resulting visual is thus the customer's, and not J+J Flooring Group's responsibility.

*NRC rating is a measure of the effectiveness of a material in absorbing sound. The higher the NRC rating, the greater the ability of the flooring product to absorb airborne noise. Independent laboratory testing of Kinetex has shown an average NRC rating of 0.33 (bare concrete flooring will typically provide a NRC Rating of 0.015).

**IIC is a rating of the insulation from impact noise. The higher the IIC rating, the greater the sound insulation. Independent laboratory testing of Kinetex has shown an average IIC Rating of .64 (bare concrete flooring will typically provide an IIC Rating of 34) NOTE: Test results and testing laboratory will vary, and the above information is not guaranteed.





www.visionary-living.com.au | www.kinetexaustralia.com

Visionary Living Commercial Floors & Walls contactus@visionary-living.com.au www.visionary-living.com.au 02 9741 6700

